

A SB024

Spun Bound Polyester Bleeder/Breather

DESCRIPTION:

A **SB024** is a spun bound, polyester felt engineered to lay smoothly on flat or low contoured parts. The low-density, straight fiber, lightweight (4 dpf) spun bound construction makes a highly efficient Breather or Bleeder and does not leave mark off like other thicker Breather/Bleeders do.

APPLICATION:

A **SB024**, when used as a bleeder, is engineered for use in standard 350°F (177°C) cure cycles using low pressures on flat or mild contoured parts. When used as a bleeder, high pressures can be used. A **SB024** is not release fabric. When used in conjunction with uncured prepregs or adhesive materials, we recommend a release film be used against the detail being cured.

SPECIFICATIONS:

Maximum use temperature:	400°F	205°C
Weight:	2.1 ± .2 oz./yd ²	71 ± 7 gms/m ²
Standard roll size:	60" x 250 yards/roll	1.52m x 228m

Custom slitting is also available.

NOTE: DATA PROVIDED IS FOR INFORMATION ONLY AND DOES NOT CONSTITUTE ANY WARRANTY FOR THE PRODUCT. AS THE CONDITIONS AND VARYING METHODS OF USE ARE BEYOND OUR CONTROL, RICHMOND AIRCRAFT PRODUCTS, INC. SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE, OR INABILITY TO USE THESE MATERIALS. THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.