

Material Safety Data Sheet



Revision Number: 003.1

Issue date: 10/28/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE® 710 LV FREKOTE	IDH number:	873889
Product type:	Mold Release	Item number:	41345
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Region:	United States
		Contact information:	Telephone: 860.571.5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

Contains one or more components for which a Toxic Substances Control Act (TSCA) Low Volume Exemption (LVE) applies. See Section 15.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Liquid	HEALTH:	*1
Color:	Colorless	FLAMMABILITY:	3
Odor:	Mild, Orange	PHYSICAL HAZARD:	0
		Personal Protection:	See MSDS Section 8

DANGER: EXTREMELY FLAMMABLE LIQUID AND VAPOR.
MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.
ASPIRATION HAZARD IF SWALLOWED.
CAN ENTER LUNGS AND CAUSE DAMAGE.
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation:	Vapors and mists will irritate nose and throat and possibly eyes. High vapor concentrations (greater than approximately 1000 ppm) may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.
Skin contact:	Solvent action can dry and defat the skin, causing the skin to crack, leading to dermatitis.
Eye contact:	Vapors may irritate eyes. Contact with eyes will cause irritation.
Ingestion:	Aspiration may occur during swallowing or vomiting, resulting in lung damage. Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.

Existing conditions aggravated by exposure: Dermatitis. Eczema. Other pre-existing skin conditions. Asthma. Other respiratory disorders (bronchitis, emphysema, bronchial hyperreactivity).

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Hexamethyldisiloxane	107-46-0	30 - 60
Solvent	Proprietary	10 - 30
Solvent	Proprietary	10 - 30
Naphtha (petroleum), light alkylate	64741-66-8	10 - 30
Proprietary Resin	Proprietary	1 - 5

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. If symptoms develop and persist, get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	Keep individual calm. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. DO NOT induce vomiting unless directed to do so by medical personnel. If vomiting occurs, prevent aspiration by keeping the patient's head below the knees. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Notes to physician:	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

5. FIRE FIGHTING MEASURES

Flash point:	-9 °C (15.8 °F) Tagliabue closed cup
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form that may ignite vapors of flammable liquids. Containers exposed to fire should be cooled with water to prevent vapor pressure buildup which could result in container rupture. If a leak or spill has not ignited, use water spray to disperse vapors. The liquid is volatile and gives off invisible vapors. Vapors are heavier than air and may travel to ignition sources and flash back.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Irritating organic fragments. Acrid smoke and fumes.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways. Prevent further leakage or spillage if safe to do so.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Wear suitable protective clothing, gloves and eye/face protection. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. For operations where eye or face contact could occur, provide safety shower and eyewash fountain. Do not wear contact lenses.

Storage: For safe storage, store at or below 48.8 °C (119.8 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Do not freeze.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Hexamethyldisiloxane	None	None	None	None
Solvent	None	None	None	None
Solvent	None	None	None	None
Naphtha (petroleum), light alkylate	None	None	None	281 ppm TWATotal Hydrocarbons
Proprietary Resin	None	None	None	None

Engineering controls: Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact. Nitrile gloves. Butyl rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Colorless

Odor: Mild, Orange
Odor threshold: Not available
pH: Not available
Vapor pressure: Not available
Boiling point/range: > 100 °C (> 212°F) (1,013 hPa)
Melting point/ range: Not available
Specific gravity: 0.8 - 0.82
Vapor density: Not available
Flash point: -9 °C (15.8 °F) Tagliabue closed cup
Flammable/Explosive limits - lower: Not available
Flammable/Explosive limits - upper: Not available
Autoignition temperature: Not available
Evaporation rate: Not determined
Solubility in water: Insoluble
Partition coefficient (n-octanol/water): Not available
VOC content: 115 g/l (calculated)

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.
Hazardous reactions: None under normal processing.
Hazardous decomposition products: Oxides of carbon. Oxides of silicon. Formaldehyde.
Incompatible materials: Oxidizing agents. Strong acids and strong bases.
Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition. Store away from incompatible materials. Do not freeze. Avoid static discharge.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Hexamethyldisiloxane	No	No	No
Solvent	No	No	No
Solvent	No	No	No
Naphtha (petroleum), light alkylate	No	No	No
Proprietary Resin	No	No	No

Hazardous components	Health Effects/Target Organs
Hexamethyldisiloxane	Irritant, Liver, Blood, Adrenals
Solvent	Irritant
Solvent	Irritant
Naphtha (petroleum), light alkylate	Irritant
Proprietary Resin	No Data

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Resin solution
Hazard class or division: 3
Identification number: UN 1866
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Resin solution
Hazard class or division: 3
Identification number: UN 1866
Packing group: II

Water Transportation (IMO/MDG)

Proper shipping name: RESIN SOLUTION (Hexamethyl disiloxane)
Hazard class or division: 3
Identification number: UN 1866
Packing group: II
Marine pollutant: Hexamethyl disiloxane

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components of this product are listed on the U.S. Toxic Substances Control Act (TSCA) inventory or are exempt from listing because a Low Volume Exemption (LVE) has been granted in accordance with 40 CFR 723.50.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health, Fire

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

WHMIS hazard class: B.2, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1, 3, 14

Prepared by: Katherine Caddy, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.