



915WB™

July 2007

PRODUCT DESCRIPTION

915WB™ provides the following product characteristics:

Technology	Cleaner
Appearance	Beige pasty liquid ^{LMS}
Chemical Type	Water based emulsion
Cure	Room temperature cure
Application	Molding

915WB™ is a water-based cleaner developed for removing residue from mold surfaces. The high-grade surfactants and emulsifiers in combination with fine abrasives give excellent results without dulling the mold surface.

TYPICAL PROPERTIES OF UNCURED MATERIAL

Density @ 25 °C, g/ml	0.97 to 0.99 ^{LMS}
Flash Point - See MSDS	
Odor	Mild Citrus

GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

Handling precautions

1. Keep away from heat, sparks and open flames

Directions for use

1. Shake 915WB™ before use. Application temperature range is 20°C - 40°C.
2. Apply product to mold surfaces with a cotton cloth or paper towel. Cloth should be wet with product but not dripping. Allow the cleaner to begin softening residue for approximately 5 minutes. **NOTE: Damp cleaner decreases removal labor.**
3. Rub or buff mold surface until residue is removed.
4. Rinse mold with water or other mild solvent.
5. **NOTE:** A simple test to assess mold cleanliness is the use of masking tape. A coated surface will allow easy release of masking tape, where as a wax free surface will allow good adhesion of masking tape. This test can also be used to determine the effectiveness of Frekote® Release Interfaces. A good interface will prevent any significant degree of tape adhesion.

Loctite Material Specification^{LMS}

LMS dated June 30, 2005. Test reports for each batch are available for the indicated properties. LMS test reports include selected QC test parameters considered appropriate to specifications for customer use. Additionally, comprehensive controls are in place to assure product quality and consistency. Special customer specification requirements may be coordinated through Henkel Quality.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.2