

A 3000 AND FR

Stretchable Polyester Bleeder/Breather

DESCRIPTION:

A 3000 is stretchable non-woven polyester felt with drapeability enabling it to conform closely to the contours of your part. The multi-directional stretch, combined with a low density lightweight construction, makes **A 3000** a highly efficient bleeder or breather.

A 3000 does not contain any binders which could close off air flow and stick to parts or other components. **A-3000** will conduct air at 50 PSI (3.5 bars) for prolonged cure cycles and in complex contours.

APPLICATION:

A 3000 is not a release fabric. When used in conjunction with uncured materials, we recommend a release film be used against the detail being cured.

A 3000 is non-toxic, non-corrosive, non-dusting and non-allergenic.

SPECIFICATIONS:

Maximum use temperature:	400°F	205°C
Weight:	4.0 +/- .4 oz./yd ²	114 +/- 14 gms/m ²
Standard roll size:	60" x 100 yards/roll	1.52m x 91.4m

A 3000 is available up to 120" (3.05m) on special order.
Custom slitting is also available.

A 3000 is also available in "Fire Retardant" (Identify as FR when ordering). FR is recommended for use in non-inert curing atmosphere. **A 3000FR** meets vertical burn test per F.A.R. Para. 25.853 (B)

NOTE: DATA PROVIDED IS FOR INFORMATION ONLY AND DOES NOT CONSTITUTE ANY WARRANTY FOR THE PRODUCT. AS THE CONDITIONS AND VARYING METHODS OF USE ARE BEYOND OUR CONTROL, RICHMOND AIRCRAFT PRODUCTS, INC. SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE, OR INABILITY TO USE THESE MATERIALS. THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.