



9225 WATSON INDUSTRIAL PARK • ST. LOUIS, MISSOURI 63126-1581
314-968-3222 • 800-325-9572 • FAX 314-968-0741
E-mail: camie@camie.com • www.camie.com

CAMIE 373 PRODUCT DATA SHEET

Camie 373 High Performance Adhesive is especially formulated to exhibit fast, aggressive tack with low soak-in for long lasting bonds, on such substrates as foam, cloth, felt, cardboard, and paper. Camie 373 is excellent for a variety of jobs for industry, display and fixtures. It can be used to bond light weight materials to a variety of substrates or itself. Camie 373 can offer temporary or permanent bonds. It is non-staining and water white in color. This product is designed to meet the flammability criteria of the FAA 12 second vertical test. FAR 25.853(a) and Appendix F part I(a)(1)(ii).

Applications	Camie 373 High Performance Adhesive can be used to bond paper, cardboard, labels and a wide variety of other substrates. See label on back container for other uses.
Container Size	24 Fluid oz. Container
Product Description	Aerosol Adhesive
Net Weight	16.25 Ounces
Cans Per Case	12
Case Dimensions-Inches	12 1/2" L X 9 3/8" W X 9 3/4" H
Case Weight	17.2 Pounds
Cases Per Pallet	80 Cases
Appearance	White
Odor	Mint When Wet
Solvent System	Isohexane, Acetone, Cyclohexane
Propellant	DME & Hydrocarbon Blend
Bond Time	15 Seconds to 2 Minutes
Heat Resistance	Max. Service Temperature 120° F
Solids	17% +/- 2%
Spray Pattern	Mist
VOC %	63.8
VOC Compliant for CA & OTC	Yes
Aerosol Flammability Level	Level 3 Aerosols
Warranty Period	One Year From Date of Shipment
Food packaging Adhesive Complies with 21CFR 175.105	No
DOT Proper Shipping Name	Consumer Commodity ORM-D for domestic ground shipment. (See MSDS for additional shipping information)



In as much as CAMIE-CAMPBELL, INC. has no control over the use to which others may put the material, it does not guarantee that the same results described herein will be obtained. Each user should make his own tests to determine the material's suitability for his own particular use.