



## TECHNICAL DATA SHEET

<b>PP Shrink Tape</b>
<b>Biaxially oriented polypropylene(BOPP)</b>

### DESCRIPTION:

**Biaxially oriented polypropylene** shrink tape is a single layer, untreated shrink tape.

### APPLICATION:

**PP Shrink Tape** is normally wrapped around the laminate on the mandrel and held in place with pressure sensitive tape. When exposed to heat, the tape shrinks, applying pressure to the part.

---

### TECHNICAL DATA:

	Typical Values
Thickness, mil:	1
Density, g/cm <sup>3</sup> :	.905
Tensile Strength	
MD, psi:	16000
TD, psi:	38000
Heat Shrinkage, %:	2
Melt Point, °F(°C):	333(167)
Heat Set Temperature, °F(°C):	280(138)
Release:	Will release from most commercially available resin systems
Burn Rate:	Slow
Shelf Life:	Indefinite

### AVAILABILITY:

**Standard widths:** 0.75" and 1.0"

Alternative widths and gauges available upon request.

Technical information furnished is based on laboratory findings and is believed to be correct. No warranties of any kind are made except that the materials are of standard quality. All risk and liabilities arising from handling, storage and use of product, as well as compliance with applicable legal restrictions rest with the buyer. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.