

***RS 200***

**Vacuum Bag Sealant Tape 400°F**

**DESCRIPTION:**

**RS 200** is a gray colored compound developed for use in composite and metal bond fabrication. **RS 200** provides maximum bag sealing security on aluminum, steel, fiberglass, nickel and graphite tool surfaces. The cure temperature limit is 400°F (205°C).

**APPLICATION:**

**RS 200** is an excellent product for bag sealing epoxies, polyesters, phenolics, and other adhesives and prepreps at temperatures ranging from 180°F to 400°F. **RS 200** strips easily and cleanly from the tool surfaces after cure.

---

**PHYSICAL PROPERTIES**

|                 |       |         |
|-----------------|-------|---------|
| Color:          | Gray  |         |
| Solids content: | 100%  |         |
| Standard sizes: |       |         |
| Width:          | 1/2"  | 12.7 mm |
| Thickness:      | 1/8"  | 3.2 mm  |
| Roll Length:    | 25'   | 7.6 m   |
| Rolls/Cs.       | 40    |         |
| Ft./Cs.         | 1,000 | 305 m   |

---

Other sizes are available on special request.  
Shelf life limitations may apply.

**NOTE:** DATA PROVIDED IS FOR INFORMATION ONLY AND DOES NOT CONSTITUTE ANY WARRANTY FOR THE PRODUCT. AS THE CONDITIONS AND VARYING METHODS OF USE ARE BEYOND OUR CONTROL, RICHMOND AIRCRAFT PRODUCTS, INC. SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE, OR INABILITY TO USE THESE MATERIALS. THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.