


P.O. Box 4980
The Woodlands, TX 77387-4980

8 am to 5 pm Phone: (800) 257-5547
24-Hour Emergency Phone: (800) 328-8501
International Emergency Phone: (409) 727-0831
Asia Pacific Emergency Phone: (65) 6336-6011

Effective Date: 10/18/06**Material Safety Data Sheet**

MSDS No: 5731

1. PRODUCT IDENTIFICATION**Trade Name:** RenLam 1310**Chemical Family:** Epoxy

NFPA RATING

Health:	3
Flammability:	1
Reactivity:	0
Personal Protection:	

HMIS RATING

Synonyms:

CGL 1310 Resin

Intended Use or Product Type:

Epoxy laminating resin

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	1333-86-4	Carbon Black Common Name: Carbon black	3.5 mg/m3	NE	3.5 mg/m3	NE	NE	Yes	NR	NR
*	2425-79-8	Oxirane, 2,2'-(1,4-Butanediylbis(Oxymethylene)]bis-Butanediol diglycidyl ether Common Name:	NE	NE	NE	NE	NE	NR	NR	NR
*	25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane Bisphenol A diglycidyl ether polymer Common Name:	NE	NE	NE	NE	NE	NR	NR	NR
*	28768-32-3	Oxiranemethanamine, N,N'-(methylenedi-4,1-phenylene)bis[N-(oxiranylmethyl)- Multifunctional epoxy resin Common Name:	NE	NE	NE	NE	NE	NR	NR	NR

Effective Date: 10/18/06

* = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Causes severe skin irritation. Causes eye irritation. May cause skin burns and allergic skin reaction.

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Carcinogenicity (NTP, IARC, OSHA): This product contains carbon black which is classified as a carcinogen by IARC (2B, possibly carcinogenic to humans) and NIOSH.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: Causes severe skin irritation. Causes eye irritation. May cause skin burns and allergic skin reaction.

Medical Conditions Aggravated by Exposure: Skin and eye conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point:	242°F (117 °C)
Flash Point Method Used:	PMCC
Flammable Limits in Air (Lower - % by volume):	Not established
Flammable Limits in Air (Upper - % by volume):	Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

Effective Date: 10/18/06

7. HANDLING AND STORAGE

Signal Word: Danger!

Precautions: Causes severe skin irritation and may cause skin burns. Can cause eye irritation and allergic skin reaction. Do not get on skin or on clothing. Avoid contact with eyes. Wash thoroughly after handling.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Black
Physical State:	Liquid
Solubility in Water:	Slight
Specific Gravity:	1.25 - 1.3 (water = 1)
Boiling Point:	Not Determined
Evaporation Rate:	Not Determined
Vapor Density:	Not Determined
VOC:	0 g/L
pH:	Not Determined

Percent Volatile: Negligible.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Effective Date: 10/18/06

Sensitization: Possible in susceptible individuals.

Carcinogenicity: This product contains carbon black which is classified as a carcinogen by IARC (2B, possibly carcinogenic to humans) and NIOSH.

Skin Irritation: Severe skin irritant.

Eye Irritation: Irritant.

Mutagenicity: Test results for N,N,N',N'-tetraglycidyl bis (para-aminophenyl) methane: ames test: positive; e.coli: negative; mouse lymphoma: positive; cell transformation: negative; nucleus anomaly (in vivo): negative; sister chromatid exchange (in vivo): inconclusive / negative; cytogenetic spermatocytes: negative; cytogenetic spermatogonia: negative. These results for N,N,N',N'-tetraglycidyl bis (para-aminophenyl) methane were filed with the EPA with a statement that the results do not seem to indicate that there is a mutagenic hazard to workers.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name: Resin compounds, N.O.I.

Department of Transportation: Not regulated as a hazardous material by the U.S. Dept. of Transportation (DOT) 49 CFR 172.101 hazardous materials table.

15. REGULATORY INFORMATION

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain any chemicals for routine annual toxic chemical release reporting under Section 313 (40 CFR 372).

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

Effective Date: 10/18/06

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Oxiranemethanamine, N,N'-(methylenedi-4,1-phenylene)bis[N-(oxiranylmethyl)-

Common Name: Multifunctional epoxy resin

CAS Number: 28768-32-3

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Oxirane, 2,2'-[1,4-Butanediylbis(Oxymethylene)]bis-

Common Name: Butanediol diglycidyl ether

CAS Number: 2425-79-8

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Limestone

Common Name: Calcium carbonate

CAS Number: 1317-65-3

Comment: Hazardous Substance

Chemical Name: Aluminum hydroxide

Common Name: Hydrated Alumina

CAS Number: 21645-51-2

Comment: Not on Pennsylvania Hazardous Substance List

16. OTHER INFORMATION

MSDS No:	5731
Approved By:	Dianne Blessing
Title:	EHS Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION

Effective Date: 10/18/06

REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.