



TACKY TAPE®
SM5143
Vacuum Bag Sealant Tape

PRODUCT DESCRIPTION:

SM5143 TACKY-TAPE® is a sealant tape developed for use in composite vacuum bagging. The tape was specifically developed for use in turbine blade manufacturing. This product has been formulated to outperform all tapes in its class. Initial tack is great and it will maintain an air-tight seal during the cure cycle, then strip clean from the mold during de-bagging. This tape has an optimum cure temperature range of room temperature to 425°F (218°C).

ADVANTAGES:

- Easy to apply by hand (User friendly)
- Ideal for oven or autoclave cure
- Uses include: debulking/compacting, envelope bagging, resin damming, or as pressure strip
- Has been shown to survive 30 debulking cycles
- Room temperature to 425°F (218°C) cure cycles
- Strips clean from tool surfaces
- Good adhesion to various films and tool surfaces
- Non-Hazardous

TYPICAL PROPERTIES:

COLOR:	Yellow
PERCENT SOLID:	100%
CONSISTENCY: Cone Penetration	75-85 300 GRAM LOAD ASTM D-217
WEIGHT/GALLON:	10.2 LBS/GALLON (1.22 Kg/L)
FREIGHT CLASSIFICATION:	Caulking Compound, NOIBN (NO LABEL REQUIRED)
STORAGE:	Keep in cool dry place. SM5143 Tacky Tape® has a 12 month shelf life from date of manufacture when stored at or below 80°F (27°C). Do not store cartons on end, keep flat.

PERFORMACE TEMPERTAURE RANGE:

Application Temperature Range: 45°F (7°C) to 120°F (49°C)
 Service Temperature Range: Room temperature to 425°F (218°C)

APPLICATION:

Apply by hand to a clean dry tool or platen with release paper on top. When the sealant is in position remove the release paper and lay the film on top. Apply pressure by hand or roller on the sealant to obtain maximum adhesion and to ensure positive vacuum. It is recommended to strip below 150°F (66°C) to minimize or reduce the parts from becoming warped. SM5143 can be stripped without leaving a residue on metal tool surfaces that have been cooled to room temperature.

PACKAGING:

SM5143 Tacky Tape[®] sealant is supplied in roll form with a special release paper. This product is available through Schnee-Morehead's Customer service department at 1-800-Trust SM (878-7876).

EXCLUSION OF WARRANTIES:

AS TO THE HEREIN DESCRIBED MATERIALS, SCHNEE-MOREHEAD[®], INC. MAKES NO WARRANTIES WHETHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SINCE THE USE OF THE HEREIN DESCRIBED MATERIALS INVOLVES MANY VARIABLES IN METHODS OF APPLICATION, HANDLING AND/OR USE, THE USER IN ACCEPTING AND USING THESE MATERIALS ASSUMES ALL RESPONSIBILITY FOR THE END RESULT. THE PURCHASE OF THIS SCHNEE-MOREHEAD[®], INC. PRODUCT IS SUBJECT TO THE TERMS AND CONDITIONS OF AN "AS IS" SALE, AND IF THE PRODUCT IS PROVED TO BE DEFECTIVE, THE EXCLUSIVE REMEDY, AT SCHNEE-MOREHEAD[®], INC.'S OPTION, SHALL BE TO REPLACE THE DEFECTIVE SCHNEE-MOREHEAD[®], INC. PRODUCT. SCHNEE-MOREHEAD[®], INC. SHALL NOT OTHERWISE BE LIABLE FOR LOSS OF DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL, REGARDLESS OF THE LEGAL THEORY ASSERTED, INCLUDING NEGLIGENCE, WARRANTY OR STRICT LIABILITY.

Complete technical information is available from Schnee-Morehead[®], Inc. For technical assistance, customer service and general information call:

1-800-TRUSTSM
1-800-878-7876

SCHNEE-MOREHEAD[®], INC.

A division of ITW
111 N. Nursery Road
Irving, TX 75060
972-438-9111 Fax: 972-554-3939
www.trustsm.com