

SHRINK TAPE III

PVA Shrink Tape

DESCRIPTION:

SHRINK TAPE III is an oriented PVA tape designed to shrink during the cure cycle and apply pressure to the composite lay-up or adhesive bond.

APPLICATION:

SHRINK TAPE III is normally wrapped over the laminate on the mold with pressure sensitive tape put in place to prevent movement during cure. The assembly is then exposed to heat and the **SHRINK TAPE III** begins applying pressure (onset of shrink) at 190°F (88°C) with maximum shrinkage at 300°F (149°C).

PHYSICAL PROPERTIES:

Roll width:	1.25" and 2.50"	3.17 cm & 6.33 cm
Roll length:	100 yards.	91.4 m
Shrinkage:	<15 % maximum	
Onset	190°F	88°C
Maximum use temperature:	300°F	149°C

Other widths are available.

NOTE: DATA PROVIDED IS FOR INFORMATION ONLY AND DOES NOT CONSTITUTE ANY WARRANTY FOR THE PRODUCT. AS THE CONDITIONS AND VARYING METHODS OF USE ARE BEYOND OUR CONTROL, RICHMOND AIRCRAFT PRODUCTS, INC. SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE, OR INABILITY TO USE THESE MATERIALS. THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
